

# AstroCel® II

## 30 mm AstroCel II Filter for Cleanroom Applications

- **Filter classification H13**
- **High efficiency mini-pleat glass fibre media**
- **Anodized aluminized cell side frame**
- **Lightweight and easy install**



The AstroCel II 30 mm air filter is designed for use in cleanroom applications. The filter is available in classification H13, with an MPPS rating of 99.95% in accordance with EN1822. This low depth filter comprises a high efficiency

mini-pleat glass fibre media pack housed in an anodized aluminized cell side frame with a faceguard on the air leavingside and a single flat gasket on the air entering side.

The filter is lightweight and easy to install.

## AstroCel® II

### Technical Data

Initial resistance	250 Pa @ 0.4 m/s
Final resistance	600 Pa
Temperature	70 C

Component	Description
Media	Waterproof, mini-pleat glass fibre
Cell sides	Anodized aluminium extrusion
Faceguard	Anodized aluminium
Gasket	5mm, half round profile, one-piece foamed gasket

### Weight & Dimensions

Part No.	Sizes (W x H x D)	Weight e.a. in kg
8218212011	610 x 1220 x 30	5.0
8218212008	610 x 610 x 30	2.5

AAF-International B.V.  
P.O. Box 7928  
1008 AC Amsterdam  
The Netherlands  
Tel.: + 31 20 549 44 11  
Fax: + 31 20 644 43 98  
www.aafeurope.com

International AAF Offices:  
Amsterdam (NL), Athens (GR), Brussels (B),  
Cramlington (GB), Dortmund (D), Dubai  
(UAE), Helsinki (Fin), Istanbul (TR), Lisbon  
(P), Louisville, Ky (USA), Madrid (E), Mexico  
(Mex), Mozzate-Co (I), Paris (F), Bangalore  
(IND), Riyadh (KSA), Shah Alam (Mal),

Suzhou, Shenzhen (PRC), Singapore,  
Taiwan, Vienna (A)

AAF Agents:  
Johannesburg (RSA)



AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

RA-1-125-IN-0307

© 2007 AAF International